

Hillstone AX-Series:

Application Delivery Controller (ADC)



Hillstone AX Series Application Delivery Controllers (ADCs) are the next generation of enterprise-class application delivery optimization products. The Hillstone ADC supports a full range of load balancing functions, including link load balancing (LLB), server load balancing (SLB) and global server load balancing (GSLB). In addition, the AX Series supports health checks for applications, servers and links, first-level network attack protection, SSL offload, application and data acceleration via caching, and more. The Hillstone ADC can greatly improve the availability and scalability of core applications and business platforms, and effectively improve the operational efficiency of enterprise data centers. Together with Hillstone security products such as next-generation firewalls, the Hillstone ADC can provide end-to-end application delivery and security capabilities for your applications and business operations.

Hillstone's ADC fully supports IPv6, high-performance clustering and carrier-grade high availability. It is widely used in server load balancing; traffic distribution and business continuity across multiple data centers; link optimization across multiple ISPs; CDN traffic management; and other application optimization and acceleration scenarios. The Hillstone ADC provides industry-leading solutions for government, finance, network operators, education, healthcare and other sectors.

Product Highlights

High-performance Server Load Balancing

Hillstone's AX Series provides server load balancing with high-capacity concurrent and new session processing capabilities. It intelligently adjusts traffic distribution based upon the health status of server nodes, and automatically completes switching to ensure the best user experience as well as application high availability. Hillstone's ADC utilizes Layer 4 to Layer 7 load balancing algorithms and load balancing based on domain names. Intelligent application identification based on characteristics, behavior and other information allows fine-tuning of performance and throughput to support employee productivity. It also supports application-layer content switching and rewrite to improve the availability of both servers and applications.

Intelligent, Efficient and Dynamic Link Load Balancing

Hillstone's AX Series ADC offers enterprise-class link load balancing technology. It features an innovative adaptive link selection control algorithm that can detect link connectivity, bandwidth utilization, delay, packet loss and jitter in real time, and adjust the traffic forwarding rules based upon the actual link quality and performance. Using an intelligent closed loop, the best route can be selected in real time so that problems such as unbalanced link utilization, single point of failure, poor cross-ISP access, wastage of link resources, and other performance problems are eliminated. The Hillstone ADC supports multiple link load balancing modes such as ECMP, ISP routing, dynamic link switching, and application routing to ensure optimal link access and support employee productivity.

High-performance SSL Offload for Secured Applications

Finance, healthcare, e-commerce and other applications are commonly secured via SSL encryption, which adds workload to servers that can impact performance and limit scalability. Hillstone's ADC supports SSL hardware acceleration technology that provides industry-leading 2048-bit SSL processing performance. By offloading SSL traffic to the Hillstone ADC's dedicated SSL processing resources, the server workload is significantly reduced resulting in improved server performance and scalability.

Full-featured IPv6

In addition to IPv6 support, the Hillstone ADC supports IPv6 application layer transformation technology to help IPv4 websites and networks seamlessly upgrade to or interoperate with IPv6. Through intelligent link processing technology, the addressing problem can be solved efficiently. The Hillstone ADC standard configuration comes with a 1T hard drive and supports log storage for the IPv6 application layer transformation.

End-to-end Security Protection

Together with Hillstone Networks' next-generation firewalls, CloudEdge, CloudHive and other security products, the Hillstone ADC can provide end-to-end security protection capabilities from network access to data centers.

Features

Server Load Balancing

- L4 and L7 server load balancing
- HTTP content switching based on URL, HTTP header, cookie, source/ destination IP, destination port, SSL/ TLS protocol and X509 certificate
- HTTP content rewriting, including external link rewriting
- Redirection for HTTP requests
- Supports Kubernetes
- Supports IPv6
- Supports HTTP2.0
- Supports WebSocket protocol
- Supports fastHTTP mode
- Support ISO 8353 compatible message based load balancing
- Supports RADIUS load balancing
- Supports MySQL load balancing with read/write splitting
- MySQL content switching based on source/ destination IP, destination port, database name, database account, and matching string
- Support clustering up to 32 devices
- Supports SMTP/POP3/IMAP mail server, perform mail load balancing in three different modes: Plaintext, SSL, STARTTLS
- Supports server connection rate limitation
- Supports multiple certificates on a virtual server

Server Health Checks

- Predefined and custom health checks for ICMP, TCP, UDP, HTTP, HTTPS, SMTP, POP3, IMAP, DNS, FTP protocol, MySQL health check, and third-party objects
- Supports email exchange protocol / RADIUS protocol health checks
- Support server resource health check
- Supports passive health check
- Supports display and statistics of health check history
- Health check logs can be delivered through SMTP and SMS

Server Session Persistence

- Source/ destination IP based and TOA based session persistence
- Supports session persistence for URL hash, HTTP header hash, session ID, request method, HTTP version, SIP CALL-ID, RDP, and Radius
- Supports session persistence for cookie including cookie hash, cookie insertion, cookie rewriting, and encrypted cookie
- Supports synchronization of session persistence table in a cluster
- Supports Set-cookie encryption and decryption

Application Acceleration

- HTTP caching (jpg, doc, ppt, xls, html, css, js, pdf, swf, mp3, avi, flv, mp4)
- TCP connection multiplexing
- Supports TCP acceleration
- HTTP compression (doc, ppt, xls, html, css, js)

SSL Inspection

- Software SSL offload; supported versions include SSLv2, SSLv3, TLS 1.0, TLS1.1, TLS1.2, TLS1.3
- SSL hardware acceleration
- Predefined or customized encryption algorithms with priorities
- SSL connection multiplexing
- Supports SSL proxy
- Works in conjunction with sBDS, NIPS and WAF to identify encrypted traffic
- Supports mirroring decrypted SSL traffic

Link Load Balancing

- Supports IP address library and ISP address library with automatic update
- Policy routing supports domain name and geographic location routing
- Supports configuration of link priority and minimum active links
- Supports IPv6

Global Server Load Balancing

- DNS server supports A, AAAA, NS, CNAME, PTR, MX, TXT, SRV
- DNS server supports recursive forwarding
- DNS supports transparent proxy deployment
- Inbound SmartDNS
- SmartDNS supports IP address library, ISP address library with automatic updates, overloaded link detection and dynamic proximity load balancing
- Support clustering multiple devices
- Supports monitoring of virtual server health status

System Management

- System management via WebUI, Console, Telnet and SSH
- Resful API supports
- Supports Ansible for automated operation and maintenance management
- Role-based authorization of administrators, auditors and operators
- Access control on the administrator address for remote management
- Supports WebUI administrators to bind to trust domain, and certificate authentication for administrators
- Configuration for password complexity and minimum length restrictions
- Supports SNMP, and synchronization of system

time from multiple NTP servers

- Supports multiple configuration files and configuration file backup and recovery
- Supports hping, tcpdump and curl operation and maintenance tools

Application Identification

- Application identification based on application characteristics, behavior and related information
- Multi-dimensional application definitions
- Thousands of application signatures
- Application signature database updated in real-time

Log and Monitoring

- Supports a variety of log types, including event logs, network logs, configuration logs, NAT logs, SLB logs, health check logs, etc.
- Log storage in both local device and server
- Email alarms and log alarms
- Real-time WebUI display of system resource utilization and hardware status
- Monitoring and graphical display of the SLB status
- Device status monitoring on mobile devices via CloudView
- Supports forwarding SLB log, health check binary log to HSA






Deployment and Network Configuration

- Supports DNS proxy
- DNS proxy blacklist and whitelist
- Deployment via one-arm reverse proxy, routing, transparent, or DSR
- Supports static routing, ISP routing, policy routing, and RIP dynamic routing protocol, and supports import of ISP information
- HA AP mode
- Supports configuration, session, health checks, PKI synchronization
- Policy control
- VSYS
- Supports AWS, Azure, Huawei Cloud and Alibaba Cloud (manual deployment only)
- Support LMS centralized authorization
- Supports VMware / KVM / Xen / Hyper-V virtualization deployment
- QoS
- Session limiting
- Supports anti-DDoS
- Supports centralized management
- Supports programmable script aRules



Specifications

	SG-6000-AX120S-IN	SG-6000-AX220S-IN	SG-6000-AX320S-IN	SG-6000-AX520S-IN
				
L4 Throughput	3 Gbps	16 Gbps	18 Gbps	35 Gbps
L4 Connections/s	40,000	110,000	110,000	270,000
L7 HTTP Throughput	1.5 Gbps	5 Gbps	7 Gbps	10 Gbps
L7 HTTP Requests/s (RPS)	80,000	200,000	200,000	540,000
Concurrent Connections	1 Million	1 Million	3 Million	10 Million
RSA 2K SSL (TPS) ⁽¹⁾	3,500	13,000	13,500	40,000
RSA 2K SSL Throughput ⁽²⁾	0.4 Gbps	1.4 Gbps	1.5 Gbps	3.4 Gbps
SSL Acceleration Technology	ASIC	ASIC	ASIC	ASIC
DNS (QPS)	19,000	39,000	40,000	95,000
Storage	480 GB SSD	480 GB SSD	480 GB SSD	960 GB SSD
Memory	4 GB	4 GB	8 GB	16 GB
Management Ports	2 x USB Ports, 1 x MGT Port, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port
GE Ports	8 (includes 1 pair bypass)	8 (includes 1 pair bypass)	16 (includes 2 pairs bypass)	16 (includes 2 pairs bypass)
GE Ports(SFP)	0	8	8	8
10GE(SFP+)	0	2	2	2, up to 6 with expansion module
40GE Ports(QSFP+)	0	0	0	0, up to 2 with expansion module
Available Slots for Expansion Modules	0	0	0	1
Expansion Module Option	N/A	N/A	N/A	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN
Power Supply	Single/ Dual AC, 100-240V	Single/ Dual AC, 100-240V	Single/ Dual AC, 100-240V	Dual AC, 100-240V, redundant hot-swappable
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Average Power	50W	50W	100W	100W
Height	1U	1U	1U	1U
Dimension (WxDxH)	17.2 x 12.6 x 1.7 in (436 x 320 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)
Net Weight	8.6 lb (3.9 kg)	9 lb (4.1 kg)	13.2 lb (6 kg)	15 lb (6.8 kg)
Gross Weight	14.3 lb (6.5 kg)	17 lb (7.7 kg)	20.7 lb (9.4 kg)	26 lb (11.8 kg)
Operating Temperature	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)
Storage Temperature	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)
Allowed Relative Humidity	10-95%, non-condensing	5-85%, non-condensing	10-95%, non-condensing	10-95%, non-condensing

Specifications (Continued)

	SG-6000-AX1200S-IN	SG-6000-AX2000-IN	SG-6000-AX2000S-IN	SG-6000-AX2200S-IN	SG-6000-AX3200S-IN
					
L4 Throughput	70 Gbps	85 Gbps	85 Gbps	85 Gbps	95 Gbps
L4 Connections/s	700,000	1 Million	1 Million	1 Million	1.2 Million
L7 HTTP Throughput	20 Gbps	40 Gbps	40 Gbps	40 Gbps	50 Gbps
L7 HTTP Requests/s (RPS)	1.4 Million	2 Million	2 Million	2 Million	2.4 Million
Concurrent Connections	20 Million	40 Million	40 Million	40 Million	40 Million
RSA 2K SSL (TPS) ⁽¹⁾	100,000	120,000	140,000	150,000	215,000
RSA 2K SSL Throughput ⁽²⁾	7 Gbps	5.5 Gbps	6 Gbps	10 Gbps	12 Gbps
SSL Acceleration Technology	ASIC	Software	ASIC	ASIC	ASIC
DNS (QPS)	240,000	350,000	350,000	420,000	460,000
Storage	960 GB SSD	1TB HDD	1TB HDD	960 GB SSD	960 GB SSD
Memory	32 GB	64 GB	64 GB	64 GB	64 GB
Management Ports	2 x USB Ports, 1 x MGT Port, 2 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port
GE Ports	8 (includes 2 pairs bypass)	2 (includes 2 MGT ports), up to 34 ports with expansion modules	2 (includes 2 MGT ports), up to 34 ports with expansion modules	8 (includes 4 pairs bypass)	8 (includes 4 pairs bypass)
GE Ports(SFP)	16	0, up to 32 with expansion module	0, up to 32 with expansion module	0	0
10GE(SFP+)	6, up to 10 with expansion module	0, up to 16 with expansion module	0, up to 16 with expansion module	16, up to 20 with expansion module	16, up to 20 with expansion module
40GE Ports(QSFP+)	0, up to 2 with expansion module	0, up to 8 with expansion module	0, up to 8 with expansion module	2, up to 4 with expansion module	2, up to 4 with expansion module
Available Slots for Expansion Modules	1	4	4	1	1
Expansion Module Option	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+H-IN, IOC-AX-4SFP+H-IN, IOC-AX-2QSFP+H-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+H-IN, IOC-AX-4SFP+H-IN, IOC-AX-2QSFP+H-IN	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN
Power Supply	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Average Power	289W	550W	550W	382W	382W
Height	1U	2U	2U	1U	1U
Dimension (WxDxH)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)
Net Weight	22.5 lb (10.2 kg)	50.7 lb (23 kg)	52.9 lb (24 kg)	22.5 lb (10.2 kg)	22.5 lb (10.2 kg)
Gross Weight	32.6 lb (14.8 kg)	61.7 lb (28 kg)	63.9 lb (29 kg)	32.6 lb (14.8 kg)	32.6 lb (14.8 kg)
Operating Temperature	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)
Storage Temperature	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)
Allowed Relative Humidity	10-95%, non-condensing	5-90%, non-condensing	5-90%, non-condensing	10-95%, non-condensing	10-95%, non-condensing

Specifications (Continued)

	SG-6000-AX4060-IN	SG-6000-AX4060S-IN	SG-6000-AX6060-IN	SG-6000-AX6060S-IN
				
L4 Throughput	130 Gbps	130 Gbps	135 Gbps	135 Gbps
L4 Connections/s	1.5 Million	1.5 Million	17.5 Million	17.5 Million
L7 HTTP Throughput	60 Gbps	60 Gbps	70 Gbps	70 Gbps
L7 HTTP Requests/s (RPS)	3 Million	3 Million	3.5 Million	3.5 Million
Concurrent Connections	40 Million	40 Million	60 Million	60 Million
RSA 2K SSL (TPS) ⁽¹⁾	170,000	190,000	260,000	260,000
RSA 2K SSL Throughput ⁽²⁾	9.5 Gbps	12 Gbps	13 Gbps	15 Gbps
SSL Acceleration Technology	Software	ASIC	Software	ASIC
DNS (QPS)	500,000	500,000	500,000	500,000
Storage	1TB HDD	1TB HDD	1TB HDD	1TB HDD
Memory	64 GB	64 GB	96 GB	96 GB
Management Ports	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port
GE Ports	2 (includes 2 MGT ports), up to 34 ports with expansion modules	2 (includes 2 MGT ports), up to 34 ports with expansion modules	2 (includes 2 MGT ports), up to 34 ports with expansion modules	2 (includes 2 MGT ports), up to 34 ports with expansion modules
GE Ports(SFP)	0, up to 32 with expansion module	0, up to 32 with expansion module	0, up to 32 with expansion module	0, up to 32 with expansion module
10GE(SFP+)	0, up to 16 with expansion module	0, up to 16 with expansion module	0, up to 16 with expansion module	0, up to 16 with expansion module
40GE Ports(QSFP+)	0, up to 8 with expansion module	0, up to 8 with expansion module	0, up to 8 with expansion module	0, up to 8 with expansion module
Available Slots for Expansion Modules	4	4	4	4
Expansion Module Option	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+-H-IN, IOC-AX-4SFP+-H-IN, IOC-AX-2QSFP+-H-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+-H-IN, IOC-AX-4SFP+-H-IN, IOC-AX-2QSFP+-H-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+-H-IN, IOC-AX-4SFP+-H-IN, IOC-AX-2QSFP+-H-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+-H-IN, IOC-AX-4SFP+-H-IN, IOC-AX-2QSFP+-H-IN
Power Supply	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Average Power	550W	550W	550W	550W
Height	2U	2U	2U	2U
Dimension (WxDxH)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)
Net Weight	50.7 lb (23 kg)	52.9 lb (24 kg)	50.7 lb (23 kg)	52.9 lb (24 kg)
Gross Weight	61.7 lb (28 kg)	63.9 lb (29 kg)	61.7 lb (28 kg)	63.9 lb (29 kg)
Operating Temperature	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)
Storage Temperature	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)
Allowed Relative Humidity	5-90%, non-condensing	5-90%, non-condensing	5-90%, non-condensing	5-90%, non-condensing

Specifications (Continued)

	SG-6000-AX02-IN	SG-6000-AX04-IN	SG-6000-AX08-IN	SG-6000-AX12-IN
CPU	2 Core	4 Core	8 Core	12 Core
HDD (min., max.)	20 GB, 1 TB	20 GB, 1 TB	20 GB, 1 TB	20 GB, 1 TB
Memory	4 GB	8 GB	16 GB	24 GB
Maximum Interfaces	10	10	10	10
L4 Throughput (SRIOV)	5 Gbps	10 Gbps	20 Gbps	30 Gbps
L4 Throughput (VMXNet3)	2 Gbps	2 Gbps	2 Gbps	2 Gbps
L7 HTTP Throughput (SRIOV)	4 Gbps	7.5 Gbps	15 Gbps	22 Gbps
L7 HTTP Throughput (VMXNet3)	2 Gbps	2 Gbps	2 Gbps	2 Gbps
L4 Connections/s	120,000	160,000	400,000	550,000
L7 HTTP Connections/s	60,000	150,000	300,000	450,000
Concurrent Connections	1 Million	3 Million	6 Million	9 Million
ECDHE RSA 2K SSL (TPS) ⁽¹⁾	3,000	4,000	5,000	14,000
ECDHE RSA 2K SSL Throughput ⁽²⁾	300 Mbps	800 Mbps	1.5 Gbps	3 Gbps

Module Options

Module	IOC-AX-4GE-B-H-IN	IOC-AX-4SFP-H-IN	IOC-AX-8GE-B-H-IN	IOC-AX-8SFP-H-IN	IOC-AX-4GE4SFP-H-IN	IOC-AX-2SFP+-H-IN
I/O Ports	4 × GE Bypass Ports	4 × SFP Ports	8 × GE Bypass Ports	8 × SFP Ports	4 × GE and 4 × SFP Ports	2 × SFP+ Ports
Dimension	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)
Weight	0.33 lb (0.15 kg)	0.33 lb (0.15 kg)	0.55 lb (0.25 kg)	0.55 lb (0.25 kg)	0.55 lb (0.25 kg)	0.33 lb (0.15 kg)

Module	IOC-AX-4SFP+-H-IN	IOC-AX-2QSFP+-H-IN	IOC-A-4SFP+-IN	IOC-A-2QSFP+-IN	IOC-A-2MM-BE-IN	IOC-A-2SM-BE-IN
I/O Ports	4 × SFP+ Ports	2 × QSFP+ Ports	4 × SFP+, SFP+ module not included	2 × QSFP+	4 × SFP, MM bypass (2 pairs of bypass ports)	4 × SFP, SM bypass (2 pairs of bypass ports)
Dimension	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U	1U	1U	1U
Weight	0.44 lb (0.2 kg)	N/A	2.09 lb (0.96 kg)	2.09 lb (0.96 kg)	2.09 lb (0.96 kg)	2.09 lb (0.96 kg)

NOTES:

- (1) In the test, Transaction Per TCP Connection uses Maximum Possible (the data of AX120S-IN/AX220S-IN/AX520S-IN/AX3200S-IN could be increased with SSL license);
 (2) The RSA key length is 2048Bit, and the encryption suite is AES256-SHA256.